Dataset Expocode 33GG20120609

**Primary Contact** Name: Pierrot, Denis

**Organization:** NOAA/Atlantic Oceanographic & Meteorological Laboratory

Address: 4301 Rickenbacker Causeway, Miami Fl, 33149

Phone: 305-361-4441

Email: Denis.Pierrot@noaa.gov

**Investigator** Name: Wanninkhof, Rik

**Organization:** NOAA/Atlantic Oceanographic & Meteorological Laboratory

Address: 4301 Rickenbacker Causeway, Miami Fl, 33149

Phone: 305-361-4379

Email: Rik.Wanninkhof@noaa.gov

**Investigator** Name: Pierrot, Denis

**Organization:** NOAA/Atlantic Oceanographic & Meteorological Laboratory

Address: 4301 Rickenbacker Causeway, Miami Fl, 33149

Phone: 305-361-4441

Email: Denis.Pierrot@noaa.gov

**Dataset** Funding Info: NOAA Climate Program Office; NOAA Ocean Acidification Program

Initial Submission (yyyymmdd): 20160330 Revised Submission (yyyymmdd): 20160330

Campaign/Cruise Expocode: 33GG20120609

Campaign/Cruise Name: GU1202\_Leg1
Campaign/Cruise Info: AOML SOOP CO2

**Platform Type:** 

CO2 Instrument Type: Equilibrator-IR or CRDS or GC

**Survey Type:** Research Cruise **Vessel Name:** R/V Gordon Gunter

Vessel Owner: NOAA Vessel Code: 33GG

Coverage Start Date (yyyymmdd): 20120610

End Date (yyyymmdd): 20120624 Westernmost Longitude: 87.2 W Easternmost Longitude: 81 W Northernmost Latitude: 30.0 N Southernmost Latitude: 23.9 N Port of Call: Pascagoula, MS Port of Call: Key West, FL

Variable Name: xCO2\_EQU\_ppm

Unit: ppm

**Description:** Mole fraction of CO2 in the equilibrator headspace (dry) at

equilibrator temperature (ppm)

Variable Name: xCO2\_ATM\_ppm

Unit: ppm

**Description:** Mole fraction of CO2 measured in dry outside air (ppm)

**Variable** Name: xCO2\_ATM\_interpolated\_ppm

Unit: ppm

**Description:** Mole fraction of CO2 in outside air associated with each water analysis. These values are interpolated between the bracketing averaged good

xCO2\_ATM analyses (ppm)

Variable Name: PRES\_EQU\_hPa

Unit: hPa

**Description:** Barometric pressure in the equilibrator headspace (hPa)

Variable Name: PRES\_ATM@SSP\_hPa

Unit: hPa

**Description:** Barometric pressure measured outside, corrected to sea level (hPa)

Variable Name: TEMP\_EQU\_C

Unit: Degree C

**Description:** Water temperature in equilibrator (°C)

Variable Name: SST\_C

Unit: Degree C

**Description:** Sea surface temperature (°C)

Variable Name: SAL permil

Unit: ppt

**Description:** Sea surface salinity on Practical Salinity Scale (o/oo)

Variable Name: fCO2\_SW@SST\_uatm

Unit: µatm

**Description:** Fugacity of CO2 in sea water at SST and 100% humidity (µatm)

Variable Name: fCO2\_ATM\_interpolated\_uatm

Unit: µatm

**Description:** Fugacity of CO2 in air corresponding to the interpolated xCO2 at SST

and 100% humidity (µatm)

Variable Name: dfCO2 uatm

Unit: µatm

**Description:** Sea water fCO2 minus interpolated air fCO2 (µatm)

Variable Name: WOCE\_QC\_FLAG

Unit: None

**Description:** Quality control flag for fCO2 values (2=good, 3=guestionable)

Variable Name: QC SUBFLAG

Unit: None

**Description:** Quality control subflag for fCO2 values, provides explanation when

QC flag=3

**Sea Surface Location:** hull mounted, ~3 m below sea surface

**Temperature Manufacturer:** Furuno

Model: T2000

Accuracy: 0.2 (°C if units not given)
Precision: 0.1 (°C if units not given)
Calibration: Factory calibration

**Comments:** Manufacturer's Resolution is taken as Precision; Maintained by ship.

Sea Surface Salinity Location: In Chem lab, next to CO2 system

Manufacturer: Seabird

Model: SBE 21

**Accuracy:** ± 0.05 o/oo **Precision:** 0.002 o/oo

**Calibration:** Factory calibration

Comments: Manufacturer's Resolution is taken as Precision; Maintained by ship.

**Atmospheric** 

Pressure

Location: Next to the bridge, ~15 m above the sea surface water

Normalized to Sea Level: yes Manufacturer: RMYoung

Model: 61201

**Accuracy:** ± 0.5 hPa (hPa if units not given) **Precision:** 0.01 hPa (hPa if units not given)

**Calibration:** Factory calibration

**Comments:** Manufacturer's Resolution is taken as Precision; Maintained by ship.

**Atmospheric CO2** 

Measured/Frequency: Yes, 5 readings in a group every 3 hours Intake Location: Bow mast, ~18 meters above sea surface

**Drying Method:** Gas stream passes through a thermoelectric condenser (~5 °C) and then through a Perma Pure (Nafion) dryer before reaching the analyzer (90%)

Atmospheric CO2 Accuracy: ± 0.5 µatm in fCO2 ATM Atmospheric CO2 Precision: ± 0.01 µatm in fCO2\_ATM

Aqueous CO2 **Equilibrator Design** 

**System Manufacturer:** Intake Depth: 5 meters Intake Location: Bow

Equilibration Type: Spray head above dynamic pool, no thermal jacket

**Equilibrator Volume (L):** 0.95 L (0.4 L water, 0.55 L headspace)

Headspace Gas Flow Rate (ml/min): 70 - 150 ml/min Equilibrator Water Flow Rate (L/min): 1.5 - 2.0 L/min

**Equilibrator Vented:** Yes

Equilibration Comments: Primary equilibrator is vented through a secondary

equilibrator.

**Drying Method:** Gas stream passes through a thermoelectric condenser (~5 °C) and then through a Perma Pure (Nafion) dryer before reaching the analyzer (90%

dry).

**Aqueous CO2 Sensor Details**  Measurement Method: IR

**Method details:** details of CO2 sensing (not required)

Manufacturer: LI-COR

Model: 7000

**Measured CO2 Values:** xco2(dry)

Measurement Frequency: Every 140 seconds, except during calibration

Aqueous CO2 Accuracy: ± 2 µatm in fCO2\_SW Aqueous CO2 Precision: ± 0.01 µatm in fCO2\_SW

**Sensor Calibrations:** 

Calibration of Calibration Gases: The analyzer is calibrated every 3 hours with field standards that in turn were calibrated with primary standards that are directly traceable to the WMO scale. The zero gas is ultra-high purity air.

Number Non-Zero Gas Standards: 3

Calibration Gases:

Std 1: LL100000, 0.00 ppm, owned by AOML, used every ~3.0 hours. Std 2: JA02267, 247.72 ppm, owned by AOML, used every ~3.0 hours. Std 3: FA02258, 399.25 ppm, owned by AOML, used every ~3.0 hours. Std 4: JA02689, 520.79 ppm, owned by AOML, used every ~3.0 hours.

**Comparison to Other CO2 Analyses:** 

Comments:

**Method Reference:** 

Pierrot, D., C. Neil, K. Sullivan, R. Castle, R. Wanninkhof, H. Lueger, T.

Johannessen, A. Olsen, R. A. Feely, and C. E. Cosca (2009), Recommendations for autonomous underway pCO2 measuring systems and data reduction routines,

Deep-Sea Res II, 56, 512-522.

Equilibrator

**Location:** Inserted into equilibrator ~5 cm below water level

**Temperature Sensor** 

Manufacturer: Hart Model: 1521

**Accuracy:** 0.025 (°C if units not given) **Precision:** 0.001 (°C if units not given)

Calibration: Factory calibration

**Comments:** Resolution is taken as Precision.

Equilibrator Pressure Sensor Location: Attached to equilibrator headspace. Combined with Licor Pressure

Manufacturer: Licor

Model: None

**Accuracy:** 1.2 (hPa if units not given) **Precision:** 0.02 (hPa if units not given)

Calibration: Factory calibration

**Comments:** Differential pressure reading from Setra-239 attached to the equilibrator headspace was added to the pressure reading from the LICOR analyzer to yield equilibrator pressure. Manufacturer's Resolution is taken as

Precision.

Additional Information

Suggested QC flag from Data Provider: NA

Additional Comments: LICOR xH2O values were negative so they were adjusted up to make standard values around 0.2 ppt. xCO2 have then be recalculated using these xH2O values. Standard xCO2 values were varying greatly (+/- 20 ppm) following the temperature of the LICOR which didn not seem to be very stable during this cruise (broken fan?). At Year Day 167 and 168, SST departed from equ T by about 1 °C - data was flagged 3. All data flagged as 3 (other-see metadata) because of the Furuno T2000 0.1 °C resolution. All original data can be found at: http://www.aoml.noaa.gov/ocd/ocdweb/gunter/gunter\_introduction.html

**Citation for this Dataset:** 

Other References for this Dataset: